

U-POL™

SAFETY DATA SHEET

FASTGLAS RESIN

Page 1

Issued: 05/12/2007

Revision No: 7

1. IDENTIFICATION OF THE SUBSTANCE / PREPARATION AND OF THE COMPANY / UNDERTAKING

Product name: FASTGLAS RESIN

Synonyms: RE/SM, RE/LA, RE/XL

GL/SM/D, GL/LA/D

Use of substance / preparation: POLYESTER RESIN CONTAINING STYRENE

Company name: U-Pol Products

Denington Industrial Estate

Denington Road

Wellingborough

Northants

NN8 2QP

United Kingdom

Tel: +44-(0)-1933 230300

Fax: +44-(0)-1933 230351

Emergency tel: +44-(0)-1933 230310

Email: technical@u-pol.com

2. HAZARDS IDENTIFICATION

Main hazards: Flammable. Harmful by inhalation. Irritating to eyes and skin.

3. COMPOSITION / INFORMATION ON INGREDIENTS

Hazardous ingredients: STYRENE 30-50%

EINECS: 202-851-5 CAS: 100-42-5

[-] R10; [Xn] R20; [Xi] R36/38

4. FIRST AID MEASURES (SYMPTOMS)

Skin contact: There may be irritation and redness at the site of contact.

Eye contact: There may be irritation and redness.

Ingestion: Nausea and stomach pain may occur.

Inhalation: There may be irritation of the throat with a feeling of tightness in the chest.

[cont...]

SAFETY DATA SHEET

FASTGLAS RESIN

4. FIRST AID MEASURES (ACTION)

Skin contact: Wash immediately with plenty of soap and water.

Eye contact: Bathe the eye with running water for 15 minutes. Consult a doctor.

Ingestion: Do not induce vomiting. Wash out mouth with water. Consult a doctor.

Inhalation: Remove casualty from exposure ensuring one's own safety whilst doing so.

5. FIRE-FIGHTING MEASURES

Extinguishing media: Carbon dioxide. Dry chemical powder. Alcohol or polymer foam.

Exposure hazards: Flammable. In combustion emits toxic fumes of carbon dioxide / carbon monoxide.

Protection of fire-fighters: Wear protective clothing to prevent contact with skin and eyes.

6. ACCIDENTAL RELEASE MEASURES

Personal precautions: Refer to section 8 of SDS for personal protection details.

Environmental precautions: Do not discharge into drains or rivers. Contain the spillage using bunding.

Clean-up procedures: Absorb into dry earth or sand.

7. HANDLING AND STORAGE

Handling requirements: Ensure there is sufficient ventilation of the area.

Storage conditions: Store in cool, well ventilated area. Keep away from sources of ignition. Keep container tightly closed.

Suitable packaging: Must only be kept in original packaging.

8. EXPOSURE CONTROLS / PERSONAL PROTECTION**Workplace exposure limits**

WEL (8 hr exposure limit): 100 ppm

WEL (15 min exposure limit): 250 ppm

Respirable dust

WEL (8 hr exposure limit): 1 mg/m³

Hazardous ingredients: STYRENE

WEL (8 hr exposure limit): 430 mg/m³ WEL (15 min exposure limit): 1080 mg/m³

Engineering measures: Ensure there is sufficient ventilation of the area.

Respiratory protection: Respiratory protective device with particle filter.

Hand protection: Nitrile gloves.

Eye protection: Safety glasses with side-shields.

Skin protection: Protective clothing.

9. PHYSICAL AND CHEMICAL PROPERTIES

State: Liquid

Colour: Yellow-gold

Odour: Aromatic

SAFETY DATA SHEET

FASTGLAS RESIN

Evaporation rate: Slow**Solubility in water:** Insoluble**Also soluble in:** Most organic solvents.**Viscosity:** Viscous**Viscosity value:** 1000 CP**Flammability limits %: lower:** 1.1**upper:** 6.1**Flash point°C:** 32**Autoflammability°C:** 490**Relative density:** 1.1**VOC g/l:** 415**10. STABILITY AND REACTIVITY****Stability:** Stable under normal conditions.**Conditions to avoid:** Direct sunlight. Heat. Sources of ignition.**Materials to avoid:** Oxidising agents.**Haz. decomp. products:** In combustion emits toxic fumes of carbon dioxide / carbon monoxide.**11. TOXICOLOGICAL INFORMATION****Hazardous ingredients:** STYRENE

IVN MUS LD50 90 mg/kg

ORL MUS LD50 316 mg/kg

ORL RAT LD50 2650 mg/kg

Routes of exposure: Refer to section 4 of SDS for routes of exposure and corresponding symptoms.**12. ECOLOGICAL INFORMATION****Mobility:** Insoluble in water. Heavier than water.**Persistence and degradability:** Not biodegradable.**Bioaccumulative potential:** No data available.**Other adverse effects:** Toxic to aquatic organisms.**13. DISPOSAL CONSIDERATIONS****Disposal operations:** D10 Incineration on land.**Disposal of packaging:** Dispose of in a regulated landfill site or other method for hazardous or toxic wastes.**NB:** The user's attention is drawn to the possible existence of regional or national regulations regarding disposal.**14. TRANSPORT INFORMATION**

SAFETY DATA SHEET
FASTGLAS RESIN**ADR / RID**

UN no: 1866 **ADR Class:** 3
Packing group: III **Classification code:** F1
Shipping name: RESIN SOLUTION
Labelling: 3 **Hazard ID no:** 30

**IMDG / IMO**

UN no: 1866 **Class:** 3
Packing group: III **EmS:** F-E,S-E
Marine pollutant: .
Labelling: 3

IATA / ICAO

UN no: 1866 **Class:** 3
Packing group: III
Packing instructions: 309(P&CA); 310(CAO)
Labelling: 3

15. REGULATORY INFORMATION

Hazard symbols: Harmful.



Risk phrases: R10: Flammable.
R20: Harmful by inhalation.
R36/38: Irritating to eyes and skin.

Safety phrases: S2: Keep out of the reach of children.
S3: Keep in a cool place.
S46: If swallowed, seek medical advice immediately and show this container or label.
S51: Use only in well-ventilated areas.

Note: The regulatory information given above only indicates the principal regulations specifically applicable to the product described in the safety data sheet. The user's attention is drawn to the possible existence of additional provisions which complete these regulations. Refer to all applicable national, international and local regulations or provisions.

SAFETY DATA SHEET
FASTGLAS RESIN

16. OTHER INFORMATION

Other information: This safety data sheet is prepared in accordance with EC Directive 2001/58/EC.
FOR PROFESSIONAL USE ONLY. Read full instructions before use.
IMPORTANT: This product contains hazardous materials and therefore appropriate personal protective equipment should always be used.
Please refer to the label and consult the material safety data sheet for full handling instructions and personal protection information. These are available via your local stockist or via the U-POL website at WWW.U-POL.COM.
U-POL disclaim any liability where the user does not wear the recommended personal protective equipment.

Risk phrases used in s.3: R10: Flammable.
R20: Harmful by inhalation.
R36/38: Irritating to eyes and skin.

Legal disclaimer: The above information is believed to be correct but does not purport to be all inclusive and shall be used only as a guide. Addition of reducers, hardeners and other additives over and above U-POL's recommendations for use, may substantially alter the composition and hazards of the product. Since conditions of use are outside our control, this company shall not be held liable for any damage resulting from handling or from contact with the above product.