



SAFETY DATA SHEET
CARLUBE ATF-U AUTOMATIC TRANSMISSION FLUID

1 IDENTIFICATION OF THE SUBSTANCE/PREPARATION AND OF THE COMPANY/UNDERTAKING

PRODUCT NAME CARLUBE ATF-U AUTOMATIC TRANSMISSION FLUID
PRODUCT NO. XTU001
INTERNAL ID A
APPLICATION Engine oil
SUPPLIER TETROSYL LIMITED
BEVIS GREEN WORKS
WALMERSLEY
BURY
BL9 6RE
0161 764 5981
0161 797 5899
info@tetrosyl.com

2 HAZARDS IDENTIFICATION

Not regarded as a health or environmental hazard under current legislation.

HUMAN HEALTH

See section 11 for additional information on health hazards.

3 COMPOSITION/INFORMATION ON INGREDIENTS

Name	EC No.	CAS-No.	Content	Classification
ALKYL ACETAMIDE			<1%	Xi;R38. R43.
DIPHENYLAMINE	204-539-4	122-39-4		T;R23/24/25 R33 N;R50/53
LONG CHAIN HYDROXYALKYLAMINE			<1%	Xi;R38. N;R51/53. R43.
MINERAL OIL	265-158-7		1-5%	Xn;R65.
POLYALKYLMETHACRYLATE			1-5%	R53.
SUBSTITUTED HYDROCARBYL SULFIDE			<1%	N;R51/53.

The Full Text for all R-Phrases are Displayed in Section 16

4 FIRST-AID MEASURES**GENERAL INFORMATION**

Remove affected person from source of contamination. Get medical attention if any discomfort continues.

NOTES TO THE PHYSICIAN

No recommendation given, but first aid may still be required in case of accidental exposure, inhalation or ingestion of this chemical. If in doubt, GET MEDICAL ATTENTION PROMPTLY!

INHALATION

Get medical attention if any discomfort continues. Place unconscious person on the side in the recovery position and ensure breathing can take place.

INGESTION

Consult a physician for specific advice.

SKIN CONTACT

Promptly wash contaminated skin with soap or mild detergent and water. Promptly remove clothing if soaked through and wash as above. Get medical attention if any discomfort continues.

CARLUBE ATF-U AUTOMATIC TRANSMISSION FLUID**EYE CONTACT**

Immediately flush with plenty of water for up to 15 minutes. Remove any contact lenses and open eyes wide apart. Get medical attention if any discomfort continues. Do not rub eye.

5 FIRE-FIGHTING MEASURES**EXTINGUISHING MEDIA**

Use fire-extinguishing media appropriate for surrounding materials.

SPECIAL FIRE FIGHTING PROCEDURES

No specific fire fighting procedure given.

PROTECTIVE MEASURES IN FIRE

Leave danger zone immediately.

6 ACCIDENTAL RELEASE MEASURES**PERSONAL PRECAUTIONS**

For personal protection, see section 8. In case of spills, beware of slippery floors and surfaces.

ENVIRONMENTAL PRECAUTIONS

The product should not be dumped in nature but collected and delivered according to agreement with the local authorities.

SPILL CLEAN UP METHODS

For waste disposal, see section 13. When dealing with a spillage, please consult the section relating to suitable protective measures. Absorb spillage with non-combustible, absorbent material. Ventilate well. Prevent discharge of larger quantity to drain.

7 HANDLING AND STORAGE**USAGE PRECAUTIONS**

Read and follow manufacturer's recommendations. Avoid spilling, skin and eye contact. Always remove grease with soap and water or skin cleaning agent, never use organic solvents. Do not eat, drink or smoke when using the product. Good personal hygiene is necessary. Wash hands and contaminated areas with water and soap before leaving the work site.

STORAGE PRECAUTIONS

Keep away from heat, sparks and open flame. Keep away from food, drink and animal feeding stuffs. Store in tightly closed original container in a dry, cool and well-ventilated place.

8 EXPOSURE CONTROLS/PERSONAL PROTECTION

Name	Std	TWA - 8 hrs		STEL - 15 min		Notes
DIPHENYLAMINE	WEL		10 mg/m3		20 mg/m3	

WEL = Workplace Exposure Limit.

PROTECTIVE EQUIPMENT**PROCESS CONDITIONS**

Use engineering controls to reduce air contamination to permissible exposure level. Provide eyewash station.

ENGINEERING MEASURES

Observe Workplace Exposure Limits and minimise the risk of inhalation of vapours.

RESPIRATORY EQUIPMENT

If ventilation is insufficient, suitable respiratory protection must be provided.

HAND PROTECTION

Use suitable protective gloves if risk of skin contact.

EYE PROTECTION

Goggles/face shield are recommended.

OTHER PROTECTION

Wear appropriate clothing to prevent reasonably probable skin contact.

CARLUBE ATF-U AUTOMATIC TRANSMISSION FLUID

HYGIENE MEASURES

Wash contaminated clothing before reuse. Wash at the end of each work shift and before eating, smoking and using the toilet.

9 PHYSICAL AND CHEMICAL PROPERTIES

APPEARANCE	Liquid		
BOILING POINT (°C)	>200	FLASH POINT (°C)	>55

10 STABILITY AND REACTIVITY

STABILITY

No particular stability concerns.

11 TOXICOLOGICAL INFORMATION

HEALTH WARNINGS

This chemical can be hazardous when inhaled and/or touched.

12 ECOLOGICAL INFORMATION

ECOTOXICITY

The product components are not classified as environmentally hazardous. However, this does not exclude the possibility that large or frequent spills can have a harmful or damaging effect on the environment.

13 DISPOSAL CONSIDERATIONS

GENERAL INFORMATION

When handling waste, consideration should be made to the safety precautions applying to handling of the product.

DISPOSAL METHODS

Dispose of waste and residues in accordance with local authority requirements. Absorb spillage with non-combustible, absorbent material.

14 TRANSPORT INFORMATION

GENERAL	The product is not covered by international regulation on the transport of dangerous goods (IMDG, IATA, ADR/RID).
---------	---

15 REGULATORY INFORMATION

RISK PHRASES

NC	Not classified.
----	-----------------

SAFETY PHRASES

P14	Contains ALKYL ACETAMIDE, LONG CHAIN HYDROXYALKYLAMINE. May produce an allergic reaction.
S2	Keep out of the reach of children
S46	If swallowed, seek medical advice immediately and show this container or label.

16 OTHER INFORMATION

REVISION COMMENTS

NOTE: Lines within the margin indicate significant changes from the previous revision.

ISSUED BY

HS&E Manager.

REVISION DATE

18/03/2008

REV. NO./REPL. SDS GENERATED 1

CARLUBE ATF-U AUTOMATIC TRANSMISSION FLUID

RISK PHRASES IN FULL

R23/24/25	Toxic by inhalation, in contact with skin and if swallowed.
R33	Danger of cumulative effects.
R38	Irritating to skin.
R43	May cause sensitisation by skin contact.
R50/53	Very toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.
R51/53	Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.
R53	May cause long-term adverse effects in the aquatic environment.
R65	Harmful: may cause lung damage if swallowed.

DISCLAIMER

The information provided in this document has been compiled on the basis of our current knowledge and is believed to be in accordance with the requirements of the Dangerous Substances Directive, Dangerous Preparations Directive and Safety Data Sheets Directive. The information relates to the specific material designated and may not be valid for such material used in combination with any other materials or in any particular conditions or process. The conditions and extent of storage and use of material are outside of our control and within the control of the possessor or user. Consequently it is the responsibility of the possessor or user to satisfy themselves as to the completeness of such information and the suitability of the material for their own particular circumstances, conditions or use.